

Centrifuge for microtubes SPECTRAFUGE 24D

- Microprocessor controlled.
- LED display for rpm or rcf reading.
- Natural air circulation, assuring a natural cooling.
- Regulable speed from 500 up to 13.000 rpm.
- Maximum rcf: 16.300 x g.
- 24 microtubes x 1,5/2 ml rotor included.
- Timer up to 30 minutes and continuous working.
- "Quick" button for momentary centrifugation.
- Dimensions: 24x29x22 cm.
- Weight: 8,1 Kg.
- 230V-50Hz

65700 SPECTRAFUGUE 24D
24 x 1,5/2ml rotor

65705 P/6 adapters for tubes 0,2 ml PCR

65706 P/6 adapters for tubes 0,5 ml PCR

65707 Adapter for strip tubes 8 x 0,2 ml PCR



Centrifuge SPECTRAFUGE MINI

- Personal sized centrifuge for microtubes.
- Maximum speed 6.000 rpm (2.000 x g).
- Supplied as standard:
 - 6 x 1,5/2ml rotor
 - Adapters for 0,5ml and 0,4ml microtubes
 - 2 strip tubes 8 x 0,2ml rotor

65730 SPECTRAFUGE MINI
6 x 1,5/2ml, Rotor 0,2ml strip tubes
Adapters for 0,5 and 0,4ml tubes

65705 P/6 adapters for 0,2ml microtubes



Personal size centrifuge for microtubes

- Lid lock system for safety.
- Speed range from 2000 up to 8000 rpm.
- Maximum rcf: 4.000 x g.
- Easy operation.
- Optional rotors for microtubes and 0,2 ml strip tubes.
- Dimensions: 20x18x14 cm.
- Weight: 3,3 Kg.
- 230V-50Hz

65720 CENTRIC BB

65721 12 x 1,5 ml rotor

65723 2 strips tubes of 8 x PCR 0,2ml rotor



Centrifuge CENTRIC 150

- Microprocessor controlled.
- Automatic rotor identification and self-diagnostic system.
- Self-limitation of speed depending of the recognized rotor.
- Unbalance detector.
- Safety device for lid opening.
- 9 Different acceleration and braking levels.
- Timer from 0,1 up to 60 minutes.
- Versatile, possibility of work with microtube rotors (0,25-2 ml) capillary and tubes up to 15 ml
- Rotors capacity: up to 24+24 microtubes, 24 capillary and 8 or 12 x 5, 7, 10 and 15 ml tubes (rotors that allows centrifuging at same time 24 x 1,5 – 2 ml microtubes and 24 x 0,25-0,5 ml)
- Regulable speed from 500 up to 13000 rpm (100 to 100 steps) or up to 16000 rpm.

65150 Microcentrifuge

- Regulable speed from 500 up to 13000 (100 to 100 steps).
- Dimensions: 275 x 330 x 240 mm.
- Weight: 15 kg.
- 230V-50/60 Hz.

Accessories:

- 65152 Rotor for 24 x 1,5/2 ml microtubes + 24 x 0,5 ml microtubes (up to 16000rpm)
- 65155 Rotor for haematocrit capillary 75x1,2mm and reader (up to 13000 rpm max)
- 65157 Rotor for 12 vacutainer, vacuette type tubes 16 x 100 (up to 5000 rpm max)
- 65159 Rotor for 8 falcon type tubes 16x120mm (up to 5000 rpm max.)
- 65059 P/12 reducers for 5 ml tubes (12x75 mm)
- 65060 P/12 reducers for 7 ml tubes(12x100 mm)



● 65150



● 65740

Centrifuge MICROLAN 160

- Microprocessor controlled.
- LED display for rpm and time reading.
- Regulable speed from 500 up to 16000 rpm.
- Max. rcf: 17000 x g.
- Include: 12 x 1,5/2 ml microtube rotor.
- Timer up to 30 minutes and continuous work.
- Safety lid

- Dimensions: 23 x 29 x 27 cm.
- Weight: 12 kg.
- Power: 250 W.
- 220V-50Hz.

65740 Centrifuge MICROLAN 160

Rotor for 12 x 1,5/2 ml tubes

65742 Rotor for 8 x 7ml tubes

Centrifuge for haematocrit tubes

- Microprocessor controller.
- LED display for rpm and time reading.
- Regulable speed from 500 up to 12.000 rpm.
- Max. rcf: 13.000 x g.
- Rotor with capacity for 12 haematocrit tubes.
- Safety lid.
- Timer up to 30 minutes and position for continuous working.
- Dimensions: 23x29x27 cm.
- Weight: 12 Kg.
- Power: 250 w.
- 220V-50Hz

65750 Centrifuge MICROLAN 170

- Rotor for 12 capillary



Centrifuge 12x15 ml

- Angle rotor for 12 x 15 ml tubes
- Regulable speed up to 4000 rpm.
- Speed analogue display in rpm.
- Timer from 0 up to 30 minutes with automatic release and position for continuous work.
- Knock off when lid is opened.
- Dimensions: 28x31x27 cm.
- Weight: 12 Kg.
- Power: 135 w.
- 220V-50Hz

65765 Centrifuge 80-2

- 12x15 ml. rotor



Centrifuge 12x15 ml

- Angle rotor for 12 x 15ml tubes.
- Regulable speed up to 4.000 r.p.m.
- Digital speed indicator in r.p.m
- Accuracy: ± 60 rpm.
- Timer from 0 up to 60 minutes with automatic release and position for continuous working.
- Safety lid.
- Dimensions: 28x31x27 cm.
- Weight: 12 Kg.
- Power: 135 w.
- 220V-50Hz

65775 Centrifuge TDL

- 12x15 ml. rotor



Centrifuge 4x100 CENTRIC

Microprocessor controlled.

Configurable parameters:

- Speed: 500-6000 rpm (depending rotors), 100 to 100 steps. Timer up to 99 minutes and continuous working (00). 10 braking positions.
- Configuration up to 15 programs.
- Self- diagnostic of working conditions, with alarms and failure indications.
- Safety device to avoid lid opening when motor is working.
- Imbalance sensor. Versatile, allows centrifuge tubes from 0,25 ml up to 100 ml, through a complet range of adapters.
- Dimensions: 343 x 400 x 440 mm.
- Weight: 28 kg
- 220V-50 Hz.



65322 Electronic centrifuge 4 x 100 ml

Accessories:

- 65332 Swing out rotor 4 places with 4 buckets (4000 rpm)
- 65390 Angle rotor for 30 x 10-12 ml tubes (30 inserts included) Vacutainer type, vacuette up to 16 x 100 mm (4.300 rpm)
- 65391 P/30 inserts for Falcon type tube 16 x 120 mm to be adapted in angle rotor 65390
- 65395 Angle rotor 6 x 50 ml (4.300 rpm) for 6 Falcon type tubes 29 x 115 mm
- 65398 Microtiter plates rotor with 2 holders. Capacity: 6 plates (3.000 rpm)

Accessories for Swing out rotor:

- 65341 Lid for bucket (P/4 units)
- 65350 Adapter for 1 x 100 ml tube (up to 44 x 100 mm)
- 65352 Adapter for 1 x 50 ml tube (up to 36 x 100 mm)
- 65353 Adapter for 1 x 50 ml – Falcon tube (up to 29 x 115mm)
- 65354 Adapter for 2 x 25 ml tubes (up to 24 x 100 mm)
- 65356 Adapter for 2 x 15 ml – Falcon tubes (up to 16 x 120 mm)
- 65358 Adapter for 6 x 12 ml Vacuette tubes (up to 16 x 100 mm)
- 65360 Adapter for 7 x 5-7 ml Vacutainer tubes (up to 12 x 75 mm)
- 65362 Adapter for 12 x 5-7ml (up to 12x75 mm)
- 65364 Adapter for 12 x 2 ml tubes (up to 11 x 40 mm)
- 65366 Adapter for 12 x 0,5 ml tubes (up to 8 x 32 mm)
- 65367 Adapter for 12 x 0,25 ml tubes (up to 6 x 30 mm)

